

# 870 Order Status Report

Functional Group ID=**RS**

## Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Order Status Report Transaction Set (870) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to report on the current status of a requirement forecast, an entire purchase order, selected line items on a purchase order, selected products/services on a purchase order, or purchase orders for a specific customer in their entirety or on a selection basis. The transaction set can also be used to report on the current status of single or multiple requisitions. The report format allows for the inclusion of "reasons" relative to the status. This transaction set may also be used to update the supplier's scheduled shipment or delivery dates. This transaction set can result from either an inquiry or a prearranged schedule agreed to by the trading partners.

## Notes:

- 1. Contractors use this transaction set to respond to a delivery status inquiry or to generate a revised delivery forecast.*
- 2. When permitted by an award instrument, this transaction set may be used by contractors to satisfy a CDRL requirement to submit delivery status reports.*
- 3. This transaction set may not be used in lieu of an 865 transaction set to request a change to the delivery requirements of an award instrument.*

## Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
Must Use	010	ST	Transaction Set Header	M	1		
Must Use	020	BSR	Beginning Segment for Order Status Report	M	1		
Not Used	040	REF	Reference Numbers	O	12		
Not Used	042	TD3	Carrier Details (Equipment)	O	1		
Not Used	043	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	1		
Not Used	044	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1		
LOOP ID - N1						200	
Must Use	050	N1	Name	O	1		
Not Used	060	N2	Additional Name Information	O	2		
Not Used	070	N3	Address Information	O	2		
Not Used	080	N4	Geographic Location	O	1		
Not Used	090	REF	Reference Numbers	O	12		
	100	PER	Administrative Communications Contact	O	3		
Not Used	105	PWK	Paperwork	O	1		
Not Used	110	DTM	Date/Time Reference	O	10		
LOOP ID - LM						10	
Not Used	120	LM	Code Source Information	O	1		
Not Used	130	LQ	Industry Code	M	100		

## Detail:

Pos.	Seg.	Req.	Loop	Notes and
003050F870_0				13 January 1997

## 870 - Order Status Report

	<u>No.</u>	<u>ID</u>	<u>Name</u>	<u>Des.</u>	<u>Max.Use</u>	<u>Repeat</u>	<u>Comments</u>
			LOOP ID - HL	1000			
Must Use	010	HL	Hierarchical Level	M	1		
Not Used	020	PRF	Purchase Order Reference	O	1		
			LOOP ID - ISR	104			
	030	ISR	Item Status Report	O	1		
Not Used	040	PID	Product/Item Description	O	6		
Not Used	050	QTY	Quantity	O	4		
	060	REF	Reference Numbers	O	12		
Not Used	070	PER	Administrative Communications Contact	O	3		
	080	DTM	Date/Time Reference	O	10		
Not Used	086	CS	Contract Summary	O	3		n1
			LOOP ID - N1	200			
	090	N1	Name	O	1		
Not Used	100	N2	Additional Name Information	O	2		
Not Used	110	N3	Address Information	O	2		
Not Used	120	N4	Geographic Location	O	1		
Not Used	130	REF	Reference Numbers	O	12		
Not Used	140	PER	Administrative Communications Contact	O	3		
			LOOP ID - LM	10			
	144	LM	Code Source Information	O	1		
Must Use	145	LQ	Industry Code	M	100		
			LOOP ID - PO1	1000			
	150	PO1	Baseline Item Data	O	1		
Not Used	155	CUR	Currency	O	1		
Not Used	160	SLN	Subline Item Detail	O	100		
Not Used	170	PO3	Additional Item Detail	O	1		
Not Used	180	PID	Product/Item Description	O	1000		
Not Used	190	MEA	Measurements	O	40		
Not Used	200	PKG	Marking, Packaging, Loading	O	25		
			LOOP ID - ISR	104			
	210	ISR	Item Status Report	O	1		
Not Used	220	PID	Product/Item Description	O	6		
	230	QTY	Quantity	O	4		
Not Used	240	DTM	Date/Time Reference	O	10		
Not Used	250	N1	Name	O	1		
Not Used	251	N2	Additional Name Information	O	2		
Not Used	252	N3	Address Information	O	2		
Not Used	253	N4	Geographic Location	O	1		
Not Used	260	TD1	Carrier Details (Quantity and Weight)	O	1		
Not Used	270	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1		
Not Used	280	TD3	Carrier Details (Equipment)	O	1		
Not Used	290	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	1		
Not Used	300	REF	Reference Numbers	O	12		
Not Used	310	SAC	Service, Promotion, Allowance, or Charge Information	O	25		
			LOOP ID - LM	10			
	320	LM	Code Source Information	O	1		

## 870 - Order Status Report

Must Use	330	LQ	Industry Code	M	100	
LOOP ID - LX >1						
Not Used	340	LX	Assigned Number	O	1	n2
Not Used	350	REF	Reference Numbers	O	>1	
Not Used	360	N1	Name	O	1	
Not Used	370	DTM	Date/Time Reference	O	10	
LOOP ID - LM 10						
Not Used	380	LM	Code Source Information	O	1	
Not Used	390	LQ	Industry Code	M	100	

**Summary:**

	<b>Pos.</b>	<b>Seg.</b>		<b>Req.</b>		<b>Loop</b>	<b>Notes and</b>
	<b>No.</b>	<b>ID</b>	<b>Name</b>	<b>Des.</b>	<b>Max.Use</b>	<b>Repeat</b>	<b>Comments</b>
Not Used	010	CTT	Transaction Totals	O	1		n3
Must Use	020	SE	Transaction Set Trailer	M	1		

**Transaction Set Notes**

1. Use is limited to intra-organizational transactions.
2. The LX loop conveys serial number, lot number, and inventory data.
3. The number of line items (CTT01) is the accumulation of the number of HL segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

**Segment:** **ST** Transaction Set Header  
**Position:** 010  
**Loop:**  
**Level:** Heading  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the start of a transaction set and to assign a control number  
**Syntax Notes:**  
**Semantic Notes:** 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).  
**Comments:**

## Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set 870 X12.23 Order Status Report	M ID 3/3
Must Use	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set <i>This unique control number is assigned by the originator of the transaction set or by the originator's application program. This same number is carried in SE02.</i>	M AN 4/9

<b>Segment:</b>	<b>BSR</b> Beginning Segment for Order Status Report
<b>Position:</b>	020
<b>Loop:</b>	
<b>Level:</b>	Heading
<b>Usage:</b>	Mandatory
<b>Max Use:</b>	1
<b>Purpose:</b>	To indicate the beginning of an Order Status Report.
<b>Syntax Notes:</b>	
<b>Semantic Notes:</b>	<ol style="list-style-type: none"> <li>1 BSR03 indicates a status report document number assigned by the sender.</li> <li>2 BSR04 indicates the date of this report from the sender.</li> <li>3 BSR07 indicates the time of this report from the sender.</li> <li>4 BSR08 indicates a status report document number assigned by the inquirer.</li> <li>5 BSR09 indicates the date this report was requested from the sender by the inquirer.</li> <li>6 BSR10 indicates the time this report was requested from the sender by the inquirer.</li> </ol>
<b>Comments:</b>	

## Data Element Summary

Ref. Des.	Data Element	Name	Attributes
Must Use BSR01	850	Status Report Code	M ID 1/2
		Code indicating the reason for sending the report	
		1 Response to an Order Status Inquiry (869)	
		2 Prearranged Schedule or Agreement	
		<i>Use to indicate this report is being submitted as a CDRL deliverable as required by an award instrument.</i>	
		3 Unsolicited Report	
		<i>Use to indicate a contractor initiated Order Status Report.</i>	
Must Use BSR02	847	Order/Item Code	M ID 1/2
		Code identifying a group of orders and items	
		<i>1. Use to identify the extent of the delivery information being provided.</i>	
		<i>2. When BSR01 is code 1, cite the same code carried in BSI03 of the 869 transaction set.</i>	
		AO All orders - items with changed status	
		<i>Use to indicate a status report is provided for all items that have previously been reported with changed delivery status on all award instruments that are not physically complete.</i>	
		CA All Orders - All Items	
		<i>1. Use to indicate a status report is provided for every item on all award instruments that are not physically complete.</i>	
		CO All Orders - Unshipped Items	
		<i>Use to indicate a status report is provided for all unshipped items on all award instruments that are not physically complete.</i>	
		PA Selected Orders - All Items	
		<i>Use to indicate a status report is provided for all items in specified orders.</i>	

			PO	Selected Orders - Unshipped Items	
				<i>Use to indicate a status report is provided for all unshipped items in specified orders.</i>	
			PP	Selected Orders - Selected Items	
				<i>Use to indicate a status report is provided for identified items in specified orders.</i>	
Must Use	BSR03	127	Reference Number	M AN 1/30	
			Reference number or identification number as defined for a particular Transaction Set, or as specified by the Reference Number Qualifier.		
			<i>Use to identify a unique number assigned to this transaction set to reference in other transaction sets, e.g., 824 Application Advice.</i>		
Must Use	BSR04	373	Date	M DT 6/6	
			Date (YYMMDD)		
			<i>Use to identify the date of this transaction set.</i>		
Not Used	BSR05	848	Product/Date Code	O ID 1/2	
			Code indicating whether the inquiry is based on products and/or date parameters		
Not Used	BSR06	849	Location Code	O ID 1/2	
			Code indicating the selection of a supplier's and/or buyer's locations or group of locations		
Not Used	BSR07	337	Time	O TM 4/8	
			Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)		
	BSR08	127	Reference Number	O AN 1/30	
			Reference number or identification number as defined for a particular Transaction Set, or as specified by the Reference Number Qualifier.		
			<i>When BSR01 is code 1, use to identify the unique reference number of the 869 Order Status Inquiry transaction set to which this transaction set is responding. This is the same number carried in BSI01 of the 869 transaction set.</i>		
Not Used	BSR09	373	Date	O DT 6/6	
			Date (YYMMDD)		
Not Used	BSR10	337	Time	O TM 4/8	
			Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)		
	BSR11	353	Transaction Set Purpose Code	O ID 2/2	
			Code identifying purpose of transaction set		
		00	Original		
			<i>Use to indicate an original report.</i>		
		01	Cancellation		
			<i>Use to indicate the cancellation of a previously transmitted 870 transaction set.</i>		
		07	Duplicate		
			<i>Use to indicate a duplicate transmission of an original report.</i>		
Not Used	BSR12	306	Action Code	O ID 1/2	
			Code indicating type of action		

<b>Segment:</b>	<b>N1</b> Name
<b>Position:</b>	050
<b>Loop:</b>	N1
<b>Level:</b>	Heading
<b>Usage:</b>	Optional (Must Use)
<b>Max Use:</b>	1
<b>Purpose:</b>	To identify a party by type of organization, name, and code
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 At least one of N102 or N103 is required.</li> <li>2 If either N103 or N104 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.</li> <li>2 N105 and N106 further define the type of entity in N101.</li> </ol>
<b>Notes:</b>	<i>At least two iterations of this N1 loop are REQUIRED, citing codes FR and TO in N101.</i>

Data Element Summary				
Ref.	Data	Name	Attributes	
Des.	Element			
Must Use	N101	98	Entity Identifier Code	M ID 2/2
			Code identifying an organizational entity, a physical location, or an individual	
		E8	Inquiring Party	
			<i>Use to indicate the party who initiated a request (869 transaction set) for the report provided, if other than the TO party.</i>	
		FR	Message From	
			<i>Use to indicate the originator of the transaction set.</i>	
		TO	Message To	
			<i>Use to indicate the recipient of the transaction set.</i>	
Not Used	N102	93	Name	X AN 1/35
			Free-form name	
	N103	66	Identification Code Qualifier	X ID 1/2
			Code designating the system/method of code structure used for Identification Code (67)	
			<i>While the federal EDI program uses the DUNS number, other government users of this implementation convention may require the use of other and additional numbers for a transition period in order to cross reference existing data bases.</i>	
		1	D-U-N-S Number, Dun & Bradstreet	
			<i>Use of the DUNs and DUNs +4 number is preferred over other codes to identify an entity.</i>	
		9	D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
			<i>Use of the DUNs and DUNs +4 number is preferred over other codes to identify an entity.</i>	
		10	Department of Defense Activity Address Code (DODAAC)	
			<i>Use to indicate a Department of Defense or Civilian Agency Activity Address Code.</i>	
		33	Commercial and Government Entity (CAGE)	
	N104	67	Identification Code	X AN 2/20
			Code identifying a party or other code	
Not Used	N105	706	Entity Relationship Code	O ID 2/2
003050F870_0				7

**Not Used   N106**

**98**

Code describing entity relationship

**Entity Identifier Code**

**O   ID 2/2**

Code identifying an organizational entity, a physical location, or an individual



**Segment:** **PER** Administrative Communications Contact  
**Position:** 100  
**Loop:** N1  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 3  
**Purpose:** To identify a person or office to whom administrative communications should be directed

**Syntax Notes:**  
**1** If either PER03 or PER04 is present, then the other is required.  
**2** If either PER05 or PER06 is present, then the other is required.  
**3** If either PER07 or PER08 is present, then the other is required.

**Semantic Notes:****Comments:**

**Notes:** *Use this segment to provide names, communication numbers, and titles of individuals associated with the entity cited in the same N1 loop.*

**Data Element Summary**

Ref. Des.	Data Element	Name	Attributes
Must Use PER01	366	<b>Contact Function Code</b> Code identifying the major duty or responsibility of the person or group named IC Information Contact	<b>M ID 2/2</b>
PER02	93	<b>Name</b> Free-form name <i>Use to identify the name of a point of contact. Last name, followed by first name, is preferred. If the whole name is longer than 35 characters, the use of initials for the first name is recommended. PER09 may be used to cite the party's title or office symbol number.</i>	<b>O AN 1/35</b>
PER03	365	<b>Communication Number Qualifier</b> Code identifying the type of communication number AU Defense Switched Network Department of Defense telecommunications system and successor of the Automatic Voice Network (AUTOVON) EM Electronic Mail FX Facsimile TE Telephone <i>Use to indicate a commercial telephone number. Include the area code.</i>	<b>X ID 2/2</b>
PER04	364	<b>Communication Number</b> Complete communications number including country or area code when applicable <i>All numbers, other than those associated with code EM, shall be transmitted as a continuous number with no extraneous characters.</i>	<b>X AN 1/80</b>
PER05	365	<b>Communication Number Qualifier</b> Code identifying the type of communication number <i>Use to identify a second communications number for the party cited in PER02. For example, if PER03/04 cites a telephone number, PER05/06 can be used to cite a FAX number.</i> AU Defense Switched Network Department of Defense telecommunications system and successor of the Automatic Voice Network	<b>X ID 2/2</b>

			(AUTOVON)
		EM	Electronic Mail
		EX	Telephone Extension
			<i>Use only if PER03 is used citing code AU or TE.</i>
		FX	Facsimile
		TE	Telephone
			<i>Use to indicate a commercial telephone number.</i>
			<i>Include the area code.</i>
<b>PER06</b>	<b>364</b>	<b>Communication Number</b>	<b>X AN 1/80</b>
		Complete communications number including country or area code when applicable	
		<i>All numbers, other than those associated with code EM, shall be transmitted as a continuous number with no extraneous characters.</i>	
<b>PER07</b>	<b>365</b>	<b>Communication Number Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type of communication number	
		<i>Use to identify a third communications number for the party cited in PER02.</i>	
		AU	Defense Switched Network
			Department of Defense telecommunications system and successor of the Automatic Voice Network (AUTOVON)
		EM	Electronic Mail
		EX	Telephone Extension
			<i>Use only if PER05 is used citing code AU or TE.</i>
		FX	Facsimile
		TE	Telephone
			<i>Use to indicate a commercial telephone number.</i>
			<i>Include the area code.</i>
<b>PER08</b>	<b>364</b>	<b>Communication Number</b>	<b>X AN 1/80</b>
		Complete communications number including country or area code when applicable	
		<i>All numbers, other than those associated with code EM, shall be transmitted as a continuous number with no extraneous characters.</i>	
<b>PER09</b>	<b>443</b>	<b>Contact Inquiry Reference</b>	<b>O AN 1/20</b>
		Additional reference number or description to clarify a contact number	
		<i>Use, if necessary, to provide the title or office symbol number of the party cited in PER02.</i>	

**Segment:** **HL** Hierarchical Level  
**Position:** 010  
**Loop:** HL  
**Level:** Detail  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To identify dependencies among and the content of hierarchically related groups of data segments

**Syntax Notes:****Semantic Notes:**

- Comments:**
- 1 The HL segment defines a top-down/left-right ordered structure.
  - 2 HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
  - 3 HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
  - 4 HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
  - 5 HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

**Notes:** 1. *This segment is used to identify the data level within a Delivery Status Report and the dependencies among various levels.*

2. *For example, if the report was being submitted at the award instrument level, HL03 would contain code IB, the award instrument number being reported would be identified in the 2/REF/060 segment the citing code CT in REF01 and the applicable status would be provided in the 2/ISR/030 segment.*

3. *If the report went down to the CLIN/SUBCLIN/ELIN level, these would be identified in the PO1 segment in PO101 and the status applicable to the CLIN/SUBCLIN/ELIN would be provided in the 2/ISR/210 loop.*

**Data Element Summary**

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	HL01	628	<b>Hierarchical ID Number</b> A unique number assigned by the sender to identify a particular data segment in a hierarchical structure <i>Use to identify a unique and progressive number assigned by the originator of the transaction set starting with the number 1.</i>	<b>M</b> AN 1/12
	HL02	734	<b>Hierarchical Parent ID Number</b> Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to <i>Use to identify a previous HL segment to which the current HL segment is subordinate. This is a number cited in HL01. For example, the second HL segment may be subordinate to the first HL segment, therefore, the number 1 would be cited; or the sixth HL segment may be subordinate to the fourth HL segment, therefore, the number 4 would be cited. If an HL segment is not subordinate to another HL segment, this data element is left blank.</i>	<b>O</b> AN 1/12

735

**Hierarchical Level Code**

M ID 1/2

Code defining the characteristic of a level in a hierarchical structure

*Use to identify the data level of the report.*

25	Subgroup	<i>Use to indicate a hierarchical level for data applicable to a specified subcontractor.</i>
B	Buyer's Location	<i>1. Use to indicate a hierarchical level for data associated with award instruments issued by a specific buying activity.</i>  <i>2. Use of this code is only necessary if a report by multiple buying offices was requested.</i>
C	Date	<i>1. Use to indicate a hierarchical level for data applicable to a specified delivery date</i>  <i>2. Use of this code is only necessary if a report by multiple delivery dates or multiple delivery date ranges was requested</i>
D	Product Description	<i>Use to indicate a hierarchical level for data identified by a product description, e.g., NSN, manufacturer part number, etc. , or by a type of service.</i>  <i>2. Use of this code is only necessary if a report by multiple product descriptions was requested. Identify the product being reported in the PO1 segment.</i>
IB	Contract	An agreement between partners  <i>Use to indicate a hierarchical level for data applicable to specified award instrument, e.g., contract, basic contract, purchase order, basic ordering agreement, etc.</i>
IC	Contract Data Requirements List (CDRL)	<i>Use to indicate a hierarchical level for data applicable to a specified exhibit.</i>
O	Order	<i>Use to indicate a hierarchical level for data applicable to a specified delivery order, call, or release.</i>
PA	Primary Administrator	<i>Use to indicate a hierarchical level for data associated with award instruments administered by a specified contract administration office.</i>  <i>2. Use of this code is only necessary if a report by multiple contract administration offices was requested.</i>
S	Shipment	<i>1. Use to indicate a hierarchical level for data applicable to a specified delivery location.</i>  <i>2. Use of this code is only necessary if a report by multiple delivery locations was requested.</i>

HL04

736

**Hierarchical Child Code**

O ID 1/1

Code indicating whether if there are hierarchical child data segments

subordinate to the level being described.

*Use to identify whether or not there are subordinate hierarchical levels to follow.*

- |   |  |
|---|--|
| 0 | No Subordinate HL Segment in This Hierarchical Structure.              |
| 1 | Additional Subordinate HL Data Segment in This Hierarchical Structure. |

**Segment:** **ISR** Item Status Report  
**Position:** 030  
**Loop:** ISR  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To specify detailed purchase order/item status  
**Syntax Notes:**  
**Semantic Notes:** 1 If ISR01 specifies a date, ISR02 is required.  
**Comments:**  
**Notes:** *Use this segment to provide the delivery status applicable to all of the items in an award instrument. If the status varies by item, use the 2/ISR/210 segment.*

## Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element		
Must Use	ISR01	368 Shipment/Order Status Code	M ID 2/2
		Code indicating the status of an order or shipment or the disposition of any difference between the quantity ordered and the quantity shipped for a line item or transaction	
		<i>Use to identify the status of the award instrument or exhibit. Where additional information regarding a delayed delivery or shipment is necessary, use the 2/LQ/145 segment to provide the information in a codified form.</i>	
		CL Complete	
		Material on the load is for one producer	
		<i>Use to indicate the completion of a service. Cite the completion date in ISR02.</i>	
		ED Expect to Ship By (Date)	
		<i>Use to indicate the date on which the contractor expects to ship the items. If the shipment date is a change from the date required to meet the contractual delivery date, cite a reason for this change in the 2/LQ/145 segment citing code 12 in LQ01.</i>	
		ID Insufficient Information	
		<i>Use to indicate the contractor has no record of the award instrument cited in REF01/02.</i>	
		IN In Process	
		<i>Use to indicate delivery will be made in accordance with the award instrument schedule.</i>	
		NY No Shipping Schedule	
		<i>Use to indicate no shipping schedule can be provided due to reasons provided in the 2/LQ/145 citing code 14 in LQ01.</i>	
		SH Shipped (Date)	
		<i>Cite the shipment date in ISR02. If more than one shipment was made, cite the last shipment date. If applicable, provide additional information in the 2/LQ/145 segment citing code 14 in LQ01.</i>	
		UN Unavailable	
		<i>Use to indicate the contractor will not perform the award instrument cited in REF01/02.</i>	
	ISR02	373 Date	O DT 6/6

Date (YYMMDD)

*When applicable, use to identify a date associated with a code cited in  
ISR01.*

**Not Used**   **ISR03****641****Status Reason Code****O**   **ID 3/3**

Code indicating the status reason

<b>Segment:</b>	<b>REF</b> Reference Numbers
<b>Position:</b>	060
<b>Loop:</b>	HL
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	12
<b>Purpose:</b>	To specify identifying numbers.
<b>Syntax Notes:</b>	<b>1</b> At least one of REF02 or REF03 is required.
<b>Semantic Notes:</b>	
<b>Comments:</b>	
<b>Notes:</b>	<i>When HL03 is code IB, IC, or O, use this segment to identify the number of the award instrument number; exhibit reference; or the delivery order, call or release.</i>

## Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Number Qualifier Code qualifying the Reference Number.	M ID 2/2
			CT Contract Number <i>When HL03 is code IB, use to indicate the number of an award instrument.</i>	
			DO Delivery Order Number <i>When HL03 is code O, use to indicate a delivery order, call or release.</i>	
			GO Exhibit Identifier <i>When HL03 is code IC, use to indicate the exhibit letter assigned to a Contract Data Requirements List (CDRL) that requires a contract deliverable being provided in this transaction set.</i>	
	REF02	127	Reference Number Reference number or identification number as defined for a particular Transaction Set, or as specified by the Reference Number Qualifier.	X AN 1/30
Not Used	REF03	352	Description A free-form description to clarify the related data elements and their content	X AN 1/80



<b>Segment:</b>	<b>DTM</b> Date/Time Reference
<b>Position:</b>	080
<b>Loop:</b>	HL
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	10
<b>Purpose:</b>	To specify pertinent dates and times
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 At least one of DTM02 DTM03 or DTM06 is required.</li> <li>2 If either DTM06 or DTM07 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	
<b>Comments:</b>	
<b>Notes:</b>	<ol style="list-style-type: none"> <li>1. When HL03 is code C, use this segment to identify the delivery dates or range of dates applicable to the report.</li> <li>2. Each DTM segment that identifies a specific delivery date or range of dates, must be associated with a specific HL segment that cites code C in HL03.</li> <li>3. If the 869 transaction set requested status for a single delivery date or range of dates, this segment is not used.</li> </ol>

## Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	DTM01	374 Date/Time Qualifier	M ID 3/3
		Code specifying type of date or time, or both date and time	
		996 Required Delivery	
		A date on which or before, ordered goods or services must be delivered	
		<i>Use to indicate the specific delivery date applicable to the report.</i>	
	DTM02	373 Date	X DT 6/6
		Date (YYMMDD)	
Not Used	DTM03	337 Time	X TM 4/8
		Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	DTM04	623 Time Code	O ID 2/2
		Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	
	DTM05	624 Century	O N0 2/2
		The first two characters in the designation of the year (CCYY)	
	DTM06	1250 Date Time Period Format Qualifier	X ID 2/3
		Code indicating the date format, time format, or date and time format	
		<i>1. Use to identify a range of dates to which the report applies.</i>	
		<i>2. The range may be both past and future dates.</i>	
		RD6 Range of Dates Expressed in Format YYMMDD-	

					YYMMDD
		RD8			Range of Dates Expressed in Format CCYYMMDD-CCYYMMDD
					A range of dates expressed in the format CCYYMMDD-CCYYMMDD where CCYY is the numerical expression of the century CC and year YY, MM is the numerical expression of the month within the year, and DD is the numerical expression of the day within the year; the first occurrence of CCYYMMDD is the beginning date and the second occurrence is the ending date
DTM07	1251	Date Time Period		X	AN 1/35
					Expression of a date, a time, or range of dates, times or dates and times

<b>Segment:</b>	<b>N1</b> Name
<b>Position:</b>	090
<b>Loop:</b>	N1
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To identify a party by type of organization, name, and code
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 At least one of N102 or N103 is required.</li> <li>2 If either N103 or N104 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.</li> <li>2 N105 and N106 further define the type of entity in N101.</li> </ol>
<b>Notes:</b>	<i>When HL03 is code S, use this segment to identify the ship-to location applicable to the report.</i>

## Data Element Summary

Ref.	Data			
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	N101	98	<b>Entity Identifier Code</b> Code identifying an organizational entity, a physical location, or an individual ST Ship To	M ID 2/2
Not Used	N102	93	<b>Name</b> Free-form name	X AN 1/35
	N103	66	<b>Identification Code Qualifier</b> Code designating the system/method of code structure used for Identification Code (67) <i>While the federal EDI program uses the DUNS number, other government users of this implementation convention may require the use of other and additional numbers for a transition period in order to cross reference existing data bases.</i> <ol style="list-style-type: none"> <li>1 D-U-N-S Number, Dun &amp; Bradstreet <i>Use of the DUNS and DUNS +4 number is preferred over other codes to identify an entity.</i></li> <li>9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix <i>Use of the DUNS and DUNS +4 number is preferred over other codes to identify an entity.</i></li> <li>10 Department of Defense Activity Address Code (DODAAC) <i>Use to indicate a Department of Defense or Civilian Agency Activity Address Code.</i></li> <li>33 Commercial and Government Entity (CAGE)</li> </ol>	X ID 1/2
	N104	67	<b>Identification Code</b> Code identifying a party or other code	X AN 2/20
Not Used	N105	706	<b>Entity Relationship Code</b> Code describing entity relationship	O ID 2/2
Not Used	N106	98	<b>Entity Identifier Code</b> Code identifying an organizational entity, a physical location, or an individual	O ID 2/2

<b>Segment:</b>	<b>LM</b> Code Source Information
<b>Position:</b>	144
<b>Loop:</b>	LM
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To transmit standard code list identification information
<b>Syntax Notes:</b>	
<b>Semantic Notes:</b>	
<b>Comments:</b>	<b>1</b> LM02 identifies the applicable industry code list source information.
<b>Notes:</b>	<i>Use this loop to identify coded data applicable to a delivery date or shipment date that applies to all of the line items in the award instrument. When the coded data varies by line item, use the 2/LM/320 loop.</i>

## Data Element Summary

Ref. Des.	Data Element	Name	Attributes
Must Use LM01	559	Agency Qualifier Code Code identifying the agency assigning the code values <i>Use any code.</i> Refer to 003050 Data Element Dictionary for acceptable code values.	M ID 2/2
LM02	822	Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier <i>When LQ01 is code ZZ, identify the code list that contains the code cited in LQ02.</i>	O AN 1/15

**Segment:** **LQ** Industry Code  
**Position:** 145  
**Loop:** LM  
**Level:** Detail  
**Usage:** Mandatory  
**Max Use:** 100  
**Purpose:** Code to transmit standard industry codes  
**Syntax Notes:** 1 If LQ01 is present, then LQ02 is required.  
**Semantic Notes:**  
**Comments:**  
**Notes:**

*Use this segment to provide coded data that provides the reason for a delivery date or shipment date cited in ISR02 or to other codes cited in ISR01.*

## Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
LQ01	1270	Code List Qualifier Code	O ID 1/3
		Code identifying a specific industry code list	
		12 Reason for Contract Delivery Date Revision Code	
		The reason why delivery of an item will not be made by the contract delivery date	
		<i>When ISR01 is code ED, use to indicate the reason for the revised delivery date.</i>	
		14 Contract Shipment Advice Code	
		Information about a shipment of material from a contractor to the government	
		<i>When ISR01 is code NY or SH, use, if applicable, to indicate additional information regarding a shipment.</i>	
		ZZ Mutually Defined	
		<i>Use to indicate that a code list is identified in LM02.</i>	
LQ02	1271	Industry Code	X AN 1/20
		Code indicating a code from a specific industry code list	
		<i>Use to cite a code that is contained in a code source list applicable to the qualifier code cited in LQ01 or when LQ01 is code ZZ, in a code source list cited in LM02.</i>	

<b>Segment:</b>	<b>PO1</b>	<b>Baseline Item Data</b>
<b>Position:</b>	150	
<b>Loop:</b>	PO1	
<b>Level:</b>	Detail	
<b>Usage:</b>	Optional	
<b>Max Use:</b>	1	
<b>Purpose:</b>	To specify basic and most frequently used line item data	
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 If PO103 is present, then PO102 is required.</li> <li>2 If PO105 is present, then PO104 is required.</li> <li>3 If either PO106 or PO107 is present, then the other is required.</li> <li>4 If either PO108 or PO109 is present, then the other is required.</li> <li>5 If either PO110 or PO111 is present, then the other is required.</li> <li>6 If either PO112 or PO113 is present, then the other is required.</li> <li>7 If either PO114 or PO115 is present, then the other is required.</li> <li>8 If either PO116 or PO117 is present, then the other is required.</li> <li>9 If either PO118 or PO119 is present, then the other is required.</li> <li>10 If either PO120 or PO121 is present, then the other is required.</li> <li>11 If either PO122 or PO123 is present, then the other is required.</li> <li>12 If either PO124 or PO125 is present, then the other is required.</li> </ol>	
<b>Semantic Notes:</b>		
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 See the Data Dictionary for a complete list of ID's.</li> <li>2 PO101 is the line item identification.</li> <li>3 PO106 through PO125 provide for ten (10) different product/service ID's per each item. For example: Case, Color, Drawing No., UPC No., ISBN No., Model No., SKU.</li> </ol>	
<b>Notes:</b>	<ol style="list-style-type: none"> <li>1. When HL03 is code IB, IC, or O, use this loop to provide delivery status for a CLIN, SUBCLIN, or ELIN applicable to an award instrument; delivery order, call, release; or exhibit. Only PO101 shall be used. Status applicable to the CLIN, SUBCLIN or ELIN will be provided in the 2/ISR/210 loop.</li> <li>2. When HL03 is code D, use this segment to identify the product to which the report applies. Only PO106/07/08/09 may be used.</li> </ol>	

## Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element		
PO101	350	<b>Assigned Identification</b>	O AN 1/11
		Alphanumeric characters assigned for differentiation within a transaction set	
		1. Use only when HL03 is code IB, IC, or O, to identify the CLIN, SUBCLIN, or ELIN.	
Not Used	PO102	<b>Quantity Ordered</b>	X R 1/9
		Quantity ordered	
Not Used	PO103	<b>Unit or Basis for Measurement Code</b>	O ID 2/2
		Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	PO104	<b>Unit Price</b>	X R 1/17
		Price per unit of product, service, commodity, etc.	
Not Used	PO105	<b>Basis of Unit Price Code</b>	O ID 2/2
		Code identifying the type of unit price for an item	
	PO106	<b>Product/Service ID Qualifier</b>	X ID 2/2
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		When HL03 is code D, use to identify the product to which the report applies.	

				CN	Commodity Name
					<i>Use to indicate the commodity name.</i>
				FS	National Stock Number
				MG	Manufacturer's Part Number
					<i>When used, PO108/09 must be used with PO108 citing either code MF or ZB.</i>
				N1	National Drug Code in 4-4-2 Format
					4-digit manufacturer ID, 4-digit product ID, 2-digit trade package size
				N2	National Drug Code in 5-3-2 Format
					5-digit manufacturer ID, 3-digit product ID, 2-digit trade package size
				N3	National Drug Code in 5-4-1 Format
					5-digit manufacturer ID, 4-digit product ID, 1-digit trade package size
				N4	National Drug Code in 5-4-2 Format
					5-digit manufacturer ID, 4-digit product ID, 2-digit trade package size
				ND	National Drug Code (NDC)
				PD	Part Number Description
					<i>Use to indicate the plain text description of an item that cannot be identified by a number.</i>
PO107	234	Product/Service ID		X	AN 1/40
Identifying number for a product or service					
PO108	235	Product/Service ID Qualifier		X	ID 2/2
Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
<i>1. When PO106 cites code MG, cite either code MF or ZB to identify the manufacturer.</i>					
<i>2. The use of code MF is preferred over code ZB as the method to identify the manufacturer of a part number.</i>					
				MF	Manufacturer
					<i>When used, cite the DUNS number of the manufacturer in the following data element.</i>
				ZB	Commercial and Government Entity (CAGE) Code
					A code that identifies a commercial contractor authorized to do business with the U.S. government
					<i>Use to indicate a manufacturer who can be identified by a CAGE code.</i>
PO109	234	Product/Service ID		X	AN 1/40
Identifying number for a product or service					
Not Used	PO110	235	Product/Service ID Qualifier	X	ID 2/2
Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
Not Used	PO111	234	Product/Service ID	X	AN 1/40
Identifying number for a product or service					
Not Used	PO112	235	Product/Service ID Qualifier	X	ID 2/2
Code identifying the type/source of the descriptive number used in Product/Service ID (234)					

<b>Not Used</b>	<b>PO113</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>
<b>Not Used</b>	<b>PO114</b>	<b>235</b>	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	<b>X</b>	<b>ID 2/2</b>
<b>Not Used</b>	<b>PO115</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>
<b>Not Used</b>	<b>PO116</b>	<b>235</b>	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	<b>X</b>	<b>ID 2/2</b>
<b>Not Used</b>	<b>PO117</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>
<b>Not Used</b>	<b>PO118</b>	<b>235</b>	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	<b>X</b>	<b>ID 2/2</b>
<b>Not Used</b>	<b>PO119</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>
<b>Not Used</b>	<b>PO120</b>	<b>235</b>	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	<b>X</b>	<b>ID 2/2</b>
<b>Not Used</b>	<b>PO121</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>
<b>Not Used</b>	<b>PO122</b>	<b>235</b>	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	<b>X</b>	<b>ID 2/2</b>
<b>Not Used</b>	<b>PO123</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>
<b>Not Used</b>	<b>PO124</b>	<b>235</b>	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	<b>X</b>	<b>ID 2/2</b>
<b>Not Used</b>	<b>PO125</b>	<b>234</b>	<b>Product/Service ID</b> Identifying number for a product or service	<b>X</b>	<b>AN 1/40</b>



<b>Segment:</b>	<b>ISR</b> Item Status Report
<b>Position:</b>	210
<b>Loop:</b>	ISR
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To specify detailed purchase order/item status
<b>Syntax Notes:</b>	
<b>Semantic Notes:</b>	1 If ISR01 specifies a date, ISR02 is required.
<b>Comments:</b>	
<b>Notes:</b>	<i>Use this segment when the delivery status varies by item within an award instrument. If the delivery status is the same for all of the items in an award instrument, use the 2/IRS/030 segment.</i>

## Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ISR01	368 Shipment/Order Status Code	M ID 2/2
		Code indicating the status of an order or shipment or the disposition of any difference between the quantity ordered and the quantity shipped for a line item or transaction	
		CL Complete	
		Material on the load is for one producer	
		<i>Use to indicate the completion of a service. Cite the completion date in ISR02.</i>	
		CP Partial Shipment on (Date), Considered No Backorder	
		<i>Use to indicate a shipment of a quantity less than the contract quantity and that the contractor considers the order complete. Identify the shipment quantity in the 2/QTY/230 segment and if applicable, provide additional information in the 2/LQ/330 segment citing code 14 in LQ01. Cite the shipment date in ISR02.</i>	
		ED Expect to Ship By (Date)	
		<i>Use to indicate the date on which the contractor expects to ship the item. If the shipment date is a change from the date required to meet the contractual delivery date, cite a reason for this change in the 2/LQ/330 segment citing code 12 in LQ01.</i>	
		IN In Process	
		<i>Use to indicate delivery will be made in accordance with the award instrument schedule.</i>	
		NY No Shipping Schedule	
		<i>Use to indicate no shipping schedule can be provided due to reasons provided in the 2/LQ/330 segment citing code 14 in LQ01.</i>	
		PR Partial Shipment	
		<i>Use to indicate a shipment of a quantity less than the contract quantity. When used, identify the quantity of the partial shipment in the 2/QTY/230 segment and, if applicable, provide additional information in the 2/LQ/330 segment citing code 14 in LQ01. Cite the shipment date in ISR02.</i>	
		SH Shipped (Date)	
		<i>Cite the shipment date in ISR02. If more than one shipment was made, cite the last shipment date. If applicable, provide additional information in the</i>	

		<i>2/LQ/330 segment citing code 14 in LQ01.</i>	
	<b>ISR02</b>	<b>373</b>	<b>Date</b> Date (YYMMDD) <i>When applicable, use to provide a date applicable to a code cited in ISR01.</i>
<b>Not Used</b>	<b>ISR03</b>	<b>641</b>	<b>Status Reason Code</b> Code indicating the status reason
		<b>O</b>	<b>DT 6/6</b>
		<b>O</b>	<b>ID 3/3</b>

**Segment:** **QTY** Quantity  
**Position:** 230  
**Loop:** ISR  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 4  
**Purpose:** To specify quantity information  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:**  
**Notes:**

*When ISR01 is code CP or PR, use to identify the quantity shipped and the portion of the shipped quantity that was inspected and accepted by the government.*

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	QTY01	673	<b>Quantity Qualifier</b> Code specifying the type of quantity 39 Shipped Quantity QA Quantity Approved Quantity allowed by the company processing the claim <i>Use to indicate the quantity of the shipment that was inspected and accepted by the government.</i>	<b>M ID 2/2</b>
Must Use	QTY02	380	<b>Quantity</b> Numeric value of quantity	<b>M R 1/15</b>
	QTY03	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 003050 Data Element Dictionary for acceptable code values.	<b>O ID 2/2</b>

**Segment:** **LM** Code Source Information  
**Position:** 320  
**Loop:** LM  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To transmit standard code list identification information  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:** 1 LM02 identifies the applicable industry code list source information.  
**Notes:** *Use this loop to provided coded data applicable to the delivery date or shipment date of the item cited in PO101.*

## Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element		
Must Use LM01	559	Agency Qualifier Code	M ID 2/2
		Code identifying the agency assigning the code values	
		<i>Use any code.</i>	
		Refer to 003050 Data Element Dictionary for acceptable code values.	
LM02	822	Source Subqualifier	O AN 1/15
		A reference that indicates the table or text maintained by the Source Qualifier	
		<i>When LQ01 is code ZZ, identify the code list that contains the code cited in LQ02.</i>	

**Segment:** **LQ** Industry Code  
**Position:** 330  
**Loop:** LM  
**Level:** Detail  
**Usage:** Mandatory  
**Max Use:** 100  
**Purpose:** Code to transmit standard industry codes  
**Syntax Notes:** 1 If LQ01 is present, then LQ02 is required.  
**Semantic Notes:**  
**Comments:**  
**Notes:**

*Use this loop to provide coded data that provides the reason for a delivery date or a shipment date for the item cited in PO101 or for coded data applicable to codes in ISR01.*

#### Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
LQ01	1270	Code List Qualifier Code	O ID 1/3
		Code identifying a specific industry code list	
		12 Reason for Contract Delivery Date Revision Code	
		The reason why delivery of an item will not be made by the contract delivery date	
		<i>When ISR01 is code ED, use to indicate the reason for the revised delivery date.</i>	
		14 Contract Shipment Advice Code	
		Information about a shipment of material from a contractor to the government	
		<i>When ISR01 is code CP, NY, PR, or SH, use, if applicable, to indicate additional information regarding a shipment.</i>	
		ZZ Mutually Defined	
		<i>Use to indicate that a code list is identified in LM02.</i>	
LQ02	1271	Industry Code	X AN 1/20
		Code indicating a code from a specific industry code list	
		<i>Use to cite a code that is contained in a code source list applicable to the qualifier code cited in LQ01 or when LQ01 is code ZZ, in a code source list cited in LM02.</i>	

**Segment:** **SE** Transaction Set Trailer  
**Position:** 020  
**Loop:**  
**Level:** Summary  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments).  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:** 1 SE is the last segment of each transaction set.

## Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	<b>Number of Included Segments</b> Total number of segments included in a transaction set including ST and SE segments	<b>M N0 1/10</b>
Must Use	SE02	329	<b>Transaction Set Control Number</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set <i>Cite the same number carried in ST02.</i>	<b>M AN 4/9</b>